



#### **SIZES**

1.5" & 3" Aperture Rings from 2 ft. to 6 ft. diameter Featuring light-leak-free lens design.



#### **MOUNTING**

Suspended - 3 or 4 Suspension Points (Power Over Suspension Cable)

## **LED LAMPING**

80/90+ CRI — Direct — 2700K/3000K/3500K/4000KOutput Options: White (1,500-14,200 lm). Custom lumen packages available upon request.

## **INTEGRATED DRIVER**

0-10V Dimming to 5% or 1%

#### **FINISH OPTIONS**

18 standard ALW finishes with no cost adder (incl. Brushed Aluminum, Satin Anodized Effect, Gloss, Basic, and Metallic Powder Coat). RAL and other stock colors from Tiger Drylac & TCI, along with custom color matching also available (setup fee applies). See alwusa.com/finishes for more details.


## **CONSTRUCTION**

All MOONRING products are hand-crafted & welded with 6061 Aluminum

## **AVAILABLE MODELS**







# **DISTRIBUTION**




Direct lamping options with lumen outputs from 1,500 to 14,200 lm.

Custom lumen packages available upon request.

### **CANOPY DIMENSIONS**





Robust canopy, crafted from rolled & welded 6061 aluminum, mounts directly to junction-box or framing

Integrated Drivers for ease-of-installation

**Understated canopy cover design** to complement virtually any ceiling. Available in virtually any powder coat finish - see alwusa.com/finishes.

## **DESIGN RESOURCES**

Start designing now with our extensive CAD, BIM (Revit), and IES file library, available at alwusa.com/cordless.

**Need some assistance?** Our sales experts are ready to help translate your vision into reality - contact us at <a href="mailto:quotes@alwusa.com">quotes@alwusa.com</a>, or (510) 489-2530.

**CONTROLS** (Contact ALW for additional compatible control systems)







105-000009 — A.O



P 510.489.2530

E TalkToUs@alwusa.com